

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 1 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

SECTION 1: Identification of the substance/mixture and of the company/undertaking	
1.1.	Product identifier
	Trade name: LOWE RUST PAINT
	Chemical name: -
	Catalogue number: -
	UFI: -
	Form: mixture
1.2.	Relevant identified uses of the substance or mixture and uses advised against
	Uses: Universal protective coat.
	Uses advised against: For some other purpose.
	Reason why uses advised against: Incompatibility
1.3.	Details of the supplier of the safety data sheet
	Supplier: Curust Industries Ltd
	Address: Unit 7, Bromley Bus.Park, Greystones, Co. Wicklow A63YW82
	Telephone number: 01 2760800
	Telefax: n/a
	e-mail of competent person: info@curust.ie
	National contact: -
1.4.	Emergency telephone number
	Medical information: 018092166



SECTION 2. Hazards identification															
2.1.	Classification of the substance or mixture														
2.1.1.	Classification according to Regulation (EC) No 1272/2008 (CLP)														
	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr style="border-bottom: 1px solid black;"> <th style="width: 50%; text-align: left; padding: 5px;">Hazard class and category code:</th> <th style="width: 50%; text-align: left; padding: 5px;">Hazard statement*:</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">Flam. Liq. 3</td> <td style="padding: 5px;">H226</td> </tr> <tr> <td style="padding: 5px;">Eye Irrit. 2</td> <td style="padding: 5px;">H319</td> </tr> <tr> <td style="padding: 5px;">STOT SE 3</td> <td style="padding: 5px;">H336</td> </tr> <tr> <td style="padding: 5px;">Aquatic Chronic 3</td> <td style="padding: 5px;">H412</td> </tr> <tr> <td></td> <td style="padding: 5px;">EUH066</td> </tr> <tr> <td></td> <td style="padding: 5px;">EUH208</td> </tr> </tbody> </table>	Hazard class and category code:	Hazard statement*:	Flam. Liq. 3	H226	Eye Irrit. 2	H319	STOT SE 3	H336	Aquatic Chronic 3	H412		EUH066		EUH208
Hazard class and category code:	Hazard statement*:														
Flam. Liq. 3	H226														
Eye Irrit. 2	H319														
STOT SE 3	H336														
Aquatic Chronic 3	H412														
	EUH066														
	EUH208														
2.1.2.	Additional information														
	-														

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 2 of 14

Trade name:	LOWE RUST PAINT			
Product code:	Date of compilation:	25.01.2023	Version:	I1

* For full text of Hazard- and EU Hazard-statements: see SECTION 16

2.2.	Label elements	
	Product identification:	LOWE RUST PAINT
	Identification number:	-
	Authorisation number:	-
	Hazard pictograms:	 
	Signal word:	Warning
	Contains:	Hydrocarbons
	Hazard statement:	H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
	Precautionary statement:	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P312 Call a POISON CENTER/doctor if you feel unwell. P501 Dispose of contents/container according to national law.
	Supplemental hazard information (EU):	EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.
2.3.	Other hazards	
		-

SECTION 3. Composition/information on ingredients

CAS/ EC/ Index number	REACH Registration No	Weight % content (or range)	Identification name	Classification according to Regulation (EC) No 1272/2008 (CLP)
64742-48-9/ 919-857-5/ -	01-2119463258- 33	35-40	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Flam. Liq. 3 STOT SE 3 Asp. Tox. 1 EUH066
107-98-2/ 203-539-1/ 603-064-00-3	01-2119457435- 35	4-5	1-methoxypropan-2-ol	Flam. Liq. 3 STOT SE 3

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 3 of 14

Trade name:	LOWE RUST PAINT			
Product code:		Date of compilation:	25.01.2023	Version: I1

1330-20-7/ 215-535-7/ 601-022-00-9	01-2119488216-32	2-3	Xylen	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2	H226 H332 H312 H315
7779-90-0/ 231-944-3/ 030-011-00-6	01-2119485044-40	1-2	Trizinc bis(orthophosphate)	Aquatic Acute 1 Aquatic Chronic 1 M(chronic)=1	H400 H410
71-36-3 200-751-6 603-004-00-6	01-2119484630-38	1-2	Butan-1-ol	Flam. Liq. 3 Acute Tox. 4 Skin Irrit. 2 Eye Dam. 1 STOT SE 3 STOT SE 3	H226 H302 H315 H318 H335 H336
1314-13-2/ 215-222-5/ 030-013-00-7	01-2119463881-32	0.2-0.5	Zinc oxide	Aquatic Acute 1 Aquatic Chronic 1 M(chronic)=1	H400 H410
27253-31-2 / 248-373-0/ -	01-2119970733-31	0.1-0.3	Neodecanoic acid, cobalt salt	STOT RE 1 Acute Tox. 4 Skin senz.1 Aquatic Chronic 3	H372 H302 H317 H412

SECTION 4. First aid measures	
4.1.	Description of first aid measures
General notes:	No information.
Following inhalation:	Remove the victim into the fresh air, put in a half-lying position and calm is. In case of the symptoms occure call a doctor and in the case of an unconscious, transfer the person to the hospital in the lateral position while maintaining the passage of the respiratory tract.
Following skin contact:	Unclothe the irrigated clothes and footwear. Contact place thoroughly rinse with water and soap about 15-20 minutes. In case of the retention symptoms, contact a doctor.
Following eye contact:	With clean fingers (wash hands first) spread shutter, aim the water in the eye (not too strong jet and not too hot water) and thereby circulate eyes so that the water come into all parts of eye. Do it at least 10-15 minutes. In case of the retention symptoms, contact a oculist.
Following ingestion:	Not cause vomiting. Rinse your mouth with water and spit out. In case of ingestion, transport the person to the nearest health institution
Self-protection of the first aider	Avoid direct contact with product and breathing vapours.
4.2.	Most important symptoms and effects, both acute and delayed
Following inhalation:	Sensitive individuals may experience headaches and dizziness.
Following skin contact:	Sensitive individuals may experience redness, itching and choking.
Following eye contact:	Direct contact may cause redness, choking, tearing.
Following ingestion:	Nausea, vomiting.

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 4 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

4.3.	Indication of any immediate medical attention and special treatment needed
	When transporting an injured person to the hospital, bring this Safety Data Sheet with you or show a label.

SECTION 5. Firefighting measures	
5.1.	Extinguishing media
	Suitable extinguishing media: Foam, CO ₂ , dry powder, water mist, soil.
	Unsuitable extinguishing media: Water-jet
5.2.	Special hazards arising from the substance or mixture
	Hazardous combustion products: Carbon oxides are formed.
5.3.	Advice for firefighters
	Relocated to safe place persons which are not directly related to the rescue process. Do not undertake any activity that involves personal risk or activity for which a person has not undergone appropriate training. Exposure to decomposition products can cause a health hazard. Use of water jet for cooling the surface not damaged tanks exposed to warmth and for protection of persons. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters. Use fireproof clothing and independent device for breathing with an open circle (EN 137). Protective clothing for firefighters (including helmets, protective boots and gloves), in accordance with the EU standard EN 469, will provide a basic level of protection for chemical incidents.
5.4.	Additional information
	-

SECTION 6. Accidental release measures	
6.1.	Personal precautions, protective equipment and emergency procedures
6.1.1.	For non-emergency personnel
	Protective equipment: According to the Section 8.
	Accident prevention methods: Remove all sources of heat or ignition. Ensure good ventilation. Stop spillage.
	Emergency procedures: Avoid direct contact with spilled material. Avoid inhaling vapour or mist. In case of major flow outs inform communication unit on number 112 according to plan interventions for environmental protection.
6.1.2.	For emergency responders:
	Use protection equipment (Section 8), and necessarily a mask for the whole face (EN 136) with filter A (EN 14387), if concentration of oxygen are not fallen below 17%. Independent device for breathing with an open circle on compress air (EN 137) use at high concentrations and if you doubt that the concentration of oxygen in air are lower than 17 %.
6.2.	Environmental precautions:

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 5 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

	Prevent discharge and spills in the water, and drainage systems, installing a sand (can be used similar materials) dam and bulkhead. Provide good ventilation. In case of major flow outs inform communication unit on number 112 according to plan interventions for environmental protection.	
6.3.	Methods and material for containment and cleaning up	
6.3.1.	Bunding, covering of drains; capping procedures:	Non-flammable adsorption materials such as sand, mineral adsorbs and the like. The drain on the floor should not be connected to sewerage.
6.3.2.	Cleaning up:	Cover with sand and transfer to containers that can be sealed hermetically.
6.3.3.	Other information:	Waste material and removed contaminated surface layer of soil should be placed in tanks that can be tightly closed, until disposal is stored in well-ventilated areas. Provide disposal to legal entities authorized to collect hazardous waste by the Ministry of Environmental Protection.
6.4.	Reference to other sections	
	Protection equipment according to the section 8 and disposal according to the section 13.	

SECTION 7. Handling and storage		
7.1.	Precautions for safe handling	
7.1.1.	Protective measures	
	Measures to prevent fire:	Keep away from fire and sources of ignition.
	Measures to prevent aerosol and dust generation:	Use the product just in good ventilated rooms.
	Measures to protect the environment:	Prevent discharge and spills in the environment.
	Other measures:	-
7.1.2.	Advice on general occupational hygiene:	
	Do not smoke, drink or eat in the room containing hazard material. Avoid inhalation and avoid eye and skin contact. In regular operating conditions wear cotton or similar working clothes, footwear which covers the entire feet, prescribed gloves from nitrile rubber and glasses or visors.	
7.2.	Conditions for safe storage, including any incompatibilities	
	Technical measures and storage conditions:	Keep away from heat and sources of ignition. Prevent the formation of static electricity.
	Packaging materials:	Original tank from producer.
	Requirements for storage rooms and vessels:	Store in tightly closed containers in a cool and well-ventilated area. Avoid storage in a room with strong oxidizing agents, strong acids, strong bases, halogens, oxidants and peroxides.
	Advices for storage equipment:	In store don't have tools or machines that can produce sparks.

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 6 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

	Further information on storage conditions:	Store separately from food, drink and animal feed.
7.3.	Specific end use(s)	
	Recommendations:	Primer and top coat for metal.
	Industrial sector specific solutions:	No information

SECTION 8. Exposure controls/personal protection

8.1.	Control parameters			
Substance	CAS No	Occupational exposure limit values/short term values		Biological limit values
		ppm	mg/m ³	
naphtha	-	100/-	400/-	-
1-methoxypropan-2-ol	107-98-2	100/150	375/568	-
xylene	1330-20-7	50/100	221/442	Blood: at the end of the work shift 14,13 µmol/l (1,50 mg/l) - taking alcohol before exposure to xylene increases the finding
butan-1-ol	71-36-3	-/50	-/154	-
Zinc oxide	1314-13-2	-/-	2R/10	-

R – respirable dust

8.2. Exposure controls

8.2.1. Appropriate engineering controls

	Substance/mixture related measures to prevent exposure during identified uses:	Use personal protection.
	Structural measures to prevent exposure:	No information
	Organisational measures to prevent exposure:	Working in well-ventilated areas. Keep containers closed.
	Technical measures to prevent exposure:	Good ventilated system.

8.2.2. Personal protection equipment:

8.2.2.1.	Eye and face protection:	Protective glasses or visor (EN 166) at lower concentrations in air, and protective mask for whole face at higher concentrations.
8.2.2.2.	Skin protection:	
	Hand protection:	At full contact of gloves from nitrile rubber with wall thickness of 0.40 mm, in contact with drops, gloves a from nitrile rubber with wall thickness of 0.11 mm (EN 374).
	Other skin protection:	In normal conditions cotton clothes and prescribed footwear (EN 13832) which cover whole foot. In the case of spillage use a apron.

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 7 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

8.2.2.3.	Respiratory protection:	At concentration higher at <i>exposure limit values</i> it's required to wear protective mask for the whole face (EN 136) with filter A (EN 371), and at concentration over a 3.000 ppm you have to use independence device for breathing with open circle on compress air (EN 137).
8.2.2.4.	Thermal hazards:	Remove all sources of ignitions.
8.2.3.	Environmental exposure controls	
	Substance/mixture related measures to prevent exposure:	Keep container tightly closed.
	Structural measures to prevent exposure:	No information
	Organisational measures to prevent exposure:	Good ventilated system.
	Technical measures to prevent exposure:	No information

SECTION 9. Physical and chemical properties

9.1.	Information on basic physical and chemical properties		
		Value	Method
	Physical state:	Viscous liquid	
	Colour:	Different shades	
	Odour/odour threshold:	By solvent	
	Melting point / freezing point;	No information	
	Boiling point or initial boiling point and boiling range:	Not applicable	
	Flammability:	No information	
	Lower and upper explosion limit:	No information	
	Flash point:	> 23°C	EN ISO 13736
	Auto-ignition temperature:	No information	
	Decomposition temperature:	No information	
	pH:	No information	
	Kinematic viscosity:	>20,5 mm ² /s	-
	Solubility:	No information	
	Partition coefficient n-octanol/water (log value):	No information	
	Vapour pressure:	No information	
	Density and/or relative density	0.95 – 1.15	EN ISO 2811-1
	Relative vapour density:	No information	
	Particle characteristics:	No information	

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 8 of 14

Trade name:	LOWE RUST PAINT			
Product code:	Date of compilation:	25.01.2023	Version:	I1

9.2.	Other information
	No information

SECTION 10. Stability and reactivity		
10.1.	Reactivity:	None reactive.
10.2.	Chemical stability:	Stable under normal conditions.
10.3.	Possibility of hazardous reactions:	Exposure to open flames or dangerous substances. Prevent the contact with heat, sparkles, flame and other sources of ignition.
10.4.	Conditions to avoid:	Sources of ignition heat and flame.
10.5.	Incompatible materials:	Strong oxidants and acids.
10.6.	Hazardous decomposition products:	None under normal operation conditions. Thermal decomposition can result with harmful gases of unknown composition.

SECTION 11. Toxicological information					
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008					
Acute toxicity:					
Route of exposure:	Method	Species	Effective Dose LD ₅₀ /LC ₅₀ or ATE _{mixture}	Exposure time	Results
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics					
Oral:	-	rat	LD ₅₀	-	5000 mg/kg
Dermal:	-	rabbit	LD ₅₀	-	3160 mg/kg
Xylen					
Oral:	-	rat	LD ₅₀	-	4300 mg/kg
Trizinc bis(orthophosphate)					
Oral:	-	rat	LD ₅₀	-	>5000 mg/kg
Inhalation:	-	rat	LD ₅₀	4h	>5,7 mg/l
Zinc oxide					
Oral:	-	rat mouse	LD ₅₀	-	>15000 mg/kg 7950 mg/kg
Inhalation:	-	rat	LD ₅₀	4h	>5,7 mg/l
Neodecanoic acid, cobalt salt					
Oral:	-	-	LD ₅₀	-	1098 mg/kg
Specific target organ toxicity – single exposure (STOT SE):					
May cause drowsiness or dizziness.					
Aspiration hazard:					

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 9 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

No information	
Irritation and corrosion:	
Skin corrosion/irritation	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	Causes serious eye irritation.
Sensitization	
Skin sensitization:	Product is not classified as sensitising but containing at least one substance classified as sensitising.
Respiratory sensitization:	No information
Symptoms related to the physical, chemical and toxicological characteristics	
Oral exposure:	No information
Dermal exposure:	No information
Inhalation exposure:	No information
Eye exposure:	No information
Repeated dose toxicity (subacute, subchronic, chronic)	
No information	
Specific target organ toxicity – repeated exposure (STOT RE):	
No information	
CMR effects (carcinogenicity; mutagenicity; reproductive toxicity)	
Carcinogenicity:	No information
Mutagenicity <i>in-vitro</i> :	No information
Genotoxicity:	No information
Mutagenicity <i>in-vivo</i> :	No information
Germ cell mutagenicity :	No information
Reproductive toxicity:	No information
Summary of evaluation of the CMR properties:	No information
11.2.	Information on other hazards:
11.2.1.	Endocrine disrupting properties:
No information	
11.2.2.	Other informations:
No information	

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 10 of 14

Trade name:	LOWE RUST PAINT				
Product code:		Date of compilation:	25.01.2023	Version:	I1

SECTION 12. Ecological information						
12.1. Toxicity						
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish:	LC ₅₀	96 h	-	-	> 1000 mg/l	-
Crustacea:	IC ₅₀	72 h	-	-	850 mg/l	-
Algae/aquatic plants:	-	-	Water flea	-	18 mg/l	-
1-methoxypropan-2-ol						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish:	LC ₅₀	-	-	-	> 1000 mg/l	-
Crustacea:	LC ₅₀	-	-	-	> 1000 mg/l	-
Algae/aquatic plants:	LC ₅₀	-	-	-	> 1000 mg/l	-
butan-1-ol						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish:	LC ₅₀	-	-	-	> 1000 mg/l	-
Crustacea:	LC ₅₀	-	-	-	> 1000 mg/l	-
Bacteria:	LC ₅₀	-	-	-	> 1000 mg/l	-
Trizinc bis(orthophosphate)						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish:	LC ₅₀	96 h	-	-	> 1000 mg/l	-
Crustacea:	EC ₅₀	48 h	-	-	> 1000 mg/l	-
Algae/aquatic plants:	ErC ₅₀	72 h	-	-	> 100 mg/l	-
Xylen						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish:	LC ₅₀	96 h	Pimephales promelas	-	13400 µg/l	-
Crustacea:	EC ₅₀	48 h	Palaemonetes pugio	-	8500 µg/l	-
12.2. Persistence and degradability						
The product is not biodegradable, the solvent evaporates.						
Biodegradation No information						
12.3. Bioaccumulative potential						

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 11 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

	Octanol-water partition coefficient (log Kow)	No information
	Bioconcentration factor (BCF)	No information
	Chronic ecotoxicity	No information
12.4.	Mobility in soil	
	Known or predicted distribution in environmental compartments:	No information
	Surface tension:	No information
	Adsorption/desorption	No information
12.5.	Results of PBT and vPvB assessment	
	No information	
12.6.	Endocrine disrupting properties	
	No information	
12.7.	Other adverse effects	
	Harmful to aquatic life with long lasting effects.	

SECTION 13. Disposal considerations	
13.1.	Waste treatment methods
13.1.1.	Product/Packaging disposal:
	Do not dispose of municipal and/or non-hazardous waste. Dispose of in accordance with valid local regulations by an authorized waste collector.
13.1.2.	Waste codes/waste designations according to Low:
	08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances. 15 01 04 Metal packaging
13.1.3.	Waste treatment – relevant information:
	Product residues are handed over to an authorised hazardous waste collector.
13.1.4.	Sewage disposal – relevant information:
	Prevent leakage and spillage into watercourses and drainage systems.

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

13.1.5.	Other disposal recommendations:
	In accordance with applicable regulations, hand over to an authorised collector.
13.1.6.	Relevant Community provisions:
	Waste Catalog

SECTION 14. Transport information	
Transporting/shipment by road (ADR)	
UN number or ID number:	-
UN proper shipping name:	-
Transport hazard class(es):	-
Packing group:	-
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by rail (RID)	
UN number:	-
UN proper shipping name:	-
Transport hazard class(es):	-
Packing group:	-
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by inland waterways (ADN)	
UN number or ID number:	-
UN proper shipping name:	-
Transport hazard class(es):	-
Packing group:	-
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by sea (IMDG)	
UN number or ID number:	-
UN proper shipping name:	-
Transport hazard class(es):	-
Packing group:	-
Environmental hazards:	-
Special precautions for user:	-
Maritime transport in bulk according to IMO instruments:	-

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 13 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

Transporting/shipment by air (ICAO-TI/IATA-DGR)	
UN number or ID number:	-
UN proper shipping name:	-
Transport hazard class(es):	-
Environmental hazards:	-
Special precautions for user:	-
Further information:	-

SECTION 15. Regulatory information	
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
	This Safety Data Sheet has been made in accordance with the comprehensive chemical legislation- REACH Regulation and Law on Chemicals and Ordinance on the Classification, Labelling, Marking and Packaging of Hazardous Chemicals.
	EU regulations
	Authorisations and/or restrictions on use
	Authorisations: No information
	Restrictions: No information
	Other EU regulations: Regulation (EC) No. 1272/2008 (CLP), REACH Regulation
	Information according 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline) A(i), 500 g/l; max. 499 g/l
	National legislation: Law on Chemicals, its regulatory acts and Ordinance on limit values of exposure to hazardous substances at work and biological limit values.
15.2.	Chemical safety assessment
	-

SECTION 16. Other information	
16.1.	Indication of changes: No information
16.2.	Abbreviations and acronyms: No information
16.3.	Key literature references and source of data: MSDS of the raw materials
16.4.	Classification and procedure used to derive the classification for mixture according to Regulation (EC) 1272/2008 (CLP)
Classification	Classification procedure

SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006

Page 14 of 14

Trade name:	LOWE RUST PAINT		
Product code:	Date of compilation:	25.01.2023	Version: I1

Flam. Liq. 3	H226	According to physio-chemical properties
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method
	EUH066	Calculation method
	EUH208	Calculation method

16.5.	Relevant H statements (number and full text)	
H:	H226 H302 H304 H312 H315 H317 H318 H332 H335 H336 H372 H400 H410 H412 EUH066 EUH208	Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains (name of sensitising substance). May produce an allergic reaction.
16.6.	Training advice:	-
16.7.	Further information:	-

ANNEX: Exposure scenario resulting to Chemical safety assessment