



Kirk Sandall Industrial Estate, Doncaster, South  
Yorkshire, DN3 1QR

+44 (0)1302 310 113  
enquiries@prosolveproducts.com  
www. prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company  
Limited  
Reg in England No: 5230722  
VAT Reg No: 381 3533 58

## TECHNICAL DATA SHEET

### PROSOLVE RENDER MESH (PVRMESH01X50)

#### DESCRIPTION

A premium woven alkali-resistant fibreglass reinforcement mesh for render or base coat plaster.

#### FEATURES:

- Lightweight
- Heavy-duty
- Waterproof – under normal usage
- Versatility – compatible with all popular plasters and renders
- Pressed weave ensures mesh cannot be pulled apart
- Economical – low-cost material with little or no waste
- Durable – tear resistant
- Easy to use – cut to size with a knife or scissors
- Safe – no sharp edges, so no protective clothing is required
- Maintenance-free – tear and alkali resistant with anti-slip properties

#### SPECIFICATION

**WEIGHT:** 160gms  $\pm$ 5

**MESH SIZE:** 4x4

**WEAVE:** Leno

**LENGTH:** 50m

**WIDTH:** 1m

**COLOUR:** Orange

**LATEX:**  $\geq$  18%

**TENSILE STRENGTH:** Warp  $\geq$  1500N/50mm and WEFT  $\geq$  1600N/50mm

*Test methods in conformity with ASTM D1668-94 and ASTM D579-90*

**NOTE:**

The products should be stored at room temperature and kept from wet and heat source.

**IMPORTANT NOTICE**

**All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.**

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.**